

40KVA Towable Generator



- 40 kVA 415 Volt
- Water Cooled
- Silenced 65dB at 7 metres
- 2 × 15amp 240volt outlets
- 1 × 20amp 415volt outlets
- 1 × 32amp 415volt outlets

Prime Power :	32kW / 40kVA 415Volts 56 Amps
Standby Power :	35kW / 44kVA
Power Factor :	0.8
Phase Voltage :	Three Phase 415 Volt
Frequency :	50 Hertz
Engine :	Forward (Previously Isuzu) 4 Cylinder Dies
RPM :	1500/min
Cooling Method :	Water Cooled - Rated For Australia's North
Alternator :	Stamford 3 Phase 4 Pole Brushless Synchron
Starter System :	12 volt Electric - Battery Included
Controller :	Comap MRS11 Series 2 Wire / Remote Start Capable

[Type here]

40KVA Towable Generator

Safety Systems :

Noise Level :

Fuel Tank Capacity :

Running Time :

Fuel Consumption :

Chassis Enclosure :

Over Temperature Protection

Over Current Protection

Low Oil / Water Protection

Battery Isolator

Emergency Stop

Failsafe Shutdown Fuel Solenoid

65 dBA at 7 metres

195 Litres (-/c Fuel Gauge)

24 Hours Continuous (prime load)

8 litres/hour (prime load)

Lockable