



- RCD Protected
- 2 x 15 Amp 240V Weatherproof IP 66 Outlets
- Key Start / Pull Start System
- Electronic Ignition
- Hour/Volt/Hertz Meter
- Maxi capacity fuel tank
- 8000 W

Prime Power :	7 kW / 7 kVA 240 Volts 29 Amps
Standby Power :	8 kW / 8 kVA
Power Factor :	1.0
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	459cc 4 stroke OHV single cylinder
RPM :	3000 rpm
Cooling Method :	Air
Power Generation :	Brushed Alternator with AVR
Starter System :	Key / Recoil Start
LCD Display :	Volts - Hertz - Hours
Noise Level :	75 dBA at 7 Metres
Oil Capacity :	1.6 Litres (10W30)
Fuel Tank Capacity :	25 Litres
Running Time :	16 Hours Continuous (Prime Load)
Fuel Consumption :	1.5 Litres/Hour (Prime Load)
Chassis Enclosure :	Open Frame
ATS (Mains Failure) :	No
RCD Protected	Yes
Single Phase Outlets :	2 x 15 Amp 240V
Three Phase Outlets :	No
Circuit Breaker :	Yes
Overload Protection :	No
Low Oil Protection :	Yes
Weight (Dry) :	90 kg
Weight (Wet) :	110 kg
Dimensions :	76 L x 69 W x 64 H cm
Carton Weight :	106 kg
Carton Dimensions :	80 L x 61 W x 70 H cm